

Filtro Baffle - Grease trap metallic filters

Filtro Baffle is a product from the "Metallic Filters" category that suits well into kitchen extracts and grease filtration. Baffle filters are made up of Stainless steel construction or Heavy Duty aluminium. These kind of filters possess a very long service life and are best suitable for kitchen hood applications. Main purpose of the filter is to trap grease from the airstream before it enters to the main duct.

Filtrowin Models

Filtro FBS

Metallic Baffle Filters with SS 304

Filtro FBA

Metallic Baffle Filters with heavy duty aluminium



Media Features and Technical Details

Filtro FBS

Filters are made up of stainless steel material. Handles are provided on filter face for easy access and maintenance. This model assures longer life and sturdiness. Filters are approved to use in high temperature due to its "all metal" construction. Filters also has a drain hole to pass grease collected.

All filters are washable using mild detergents in hot water. Very strong grease loading can be removed using stronger cleansing liquids provided they are non-caustic. Wash the filters well, rinse and dry well before next use.

Filtro FBA

Filters are made up of heavy duty aluminium. Handles are provided on filter face for easy access and maintenance. This model assures longer life and sturdiness. Filters are approved to use in high temperature due to its "all metal" construction. Filters also has a drain hole to pass grease collected.

All filters are washable using mild detergents in hot water. Very strong grease loading can be removed using stronger cleansing liquids provided they are non-caustic. Wash the filters well, rinse and dry well before next use.

Selection Chart ▼

Models	Nominal Size (mm)	Airflow (CMH)	IPD - Pa (1.75m/s / 2.5m/s)
FBS-24-2	287 x 592 x 45	1700	20 / 30
FBS-60-2	395 x 495 x 45	1880	20 / 30
FBS-65-2	395 x 622 x 45	2380	20 / 30
FBS-00-2	495 x 495 x 45	2380	20 / 30
FBS-05-2	495 x 622 x 45	2975	20 / 30
FBS-44-2	592 x 592 x 45	3400	20 / 30

Models	Nominal Size (mm)	Airflow (CMH)	IPD - Pa (1.75m/s / 2.5m/s)
FBA-24-2	287 x 592 x 45	1700	20 / 30
FBA-60-2	395 x 495 x 45	1880	20 / 30
FBA-65-2	395 x 622 x 45	2380	20 / 30
FBA-00-2	495 x 495 x 45	2380	20 / 30
FBA-05-2	495 x 622 x 45	2975	20 / 30
FBA-44-2	592 x 592 x 45	3400	20 / 30

● Contact factory for non-standard dimensions

All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notices due to the constant technical improvement.

© Copyright: Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. We assume no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

