

Filtro Cell V - Mini Pleat Compact Pocket Filters

Filtro Cell V, the high efficiency Mini-Pleat compact filters made up of micro-fine glass fiber media are available in a wide range of efficiencies from M6 - F9 (65% - 95%+). Filtro Cell V are designed to use in HVAC installations where highest degree of air cleanliness is required. The compact design, larger surface area and low initial resistance made it an ideal alternative to ordinary Bag filters & Box type filters of the similar efficiencies. Filtro Cell V models are also available with very high burst resistance, low pressure drop and high dust holding capacity for extreme operating conditions like Gas turbine air intake fine filtration etc. Filtro Cell VGT Models are available with plastic grid support optional.


Filtrowin Models

Filtro Cell V

Minipleat Compact Filters in plastic frame with 292mm depth
Available in 20 and 25mm headers

Filtro Cell VGT

Minipleat Compact Filters in plastic frame with 292mm depth
backed with plastic mesh support for additional protection
Available in 20 and 25mm headers




Media Features and Technical Details

FILTRO CELL V filters are made up of water resistant micro-fine glass fiber filter media, closely pleated and separated by continuous thermoplastic bead separators. This design accommodates a very large quantity of filter media which offers a longer service life and low pressure drop. The Mini-Pleated media packs are arranged in perfect V design and sealed to the enclosing frame. Single piece PU foam gasket will be provided upon request.

The VGT model filters utilize a special grade media offering very high dust holding capacity and the mini-pleat packs are backed with an additional plastic grid support for each media panel to ensure protection during operation at harsh conditions. Fully Potted versions are also available. Filters are absolutely metal free and so are incinerable and environmentally friendly. Filters can also be made in Reverse flow design. These filters offer very high burst pressure, hence ideal for extreme operating conditions like Gas turbine air intake applications.

Filtro Cell V - Airflow vs. Initial Resistance



Selection Chart ▼

ASHRAE 52.2 / EN 779 : 2012	Arrestance (%)	Model	GT Model	Size (mm)	Rated Airflow (CMH)		Initial Resistance (Pa)		Final Resistance (Pa)
					@2.54 m/s	@3.17 m/s	2.54 m/s	3.17 m/s	
MERV 15 / F9	99.9	FVG9-44-12	FVGT9-44-12	Size: 592 x 592 x 292	3400	4250	135	175	635
MERV 15 / F9	99.9	FVG9-04-12	FVGT9-04-12	Size: 490 x 592 x 292	2750	3450	135	175	635
MERV 15 / F9	99.9	FVG9-24-12	FVGT9-24-12	Size: 287 x 592 x 292	1700	2125	135	175	635
MERV 14 / F8	99.9	FVG8-44-12	FVGT8-44-12	Size: 592 x 592 x 292	3400	4250	95	125	635
MERV 14 / F8	99.9	FVG8-04-12	FVGT8-04-12	Size: 490 x 592 x 292	2750	3450	95	125	635
MERV 14 / F8	99.9	FVG8-24-12	FVGT8-24-12	Size: 287 x 592 x 292	1700	2125	95	125	635
MERV 13 / F7	99	FVG7-44-12	FVGT7-44-12	Size: 592 x 592 x 292	3400	4250	80	105	635
MERV 13 / F7	99	FVG7-04-12	FVGT7-04-12	Size: 490 x 592 x 292	2750	3450	80	105	635
MERV 13 / F7	99	FVG7-24-12	FVGT7-24-12	Size: 287 x 592 x 292	1700	2125	80	105	635
MERV 11 / M6	98	FVG6-44-12	FVGT6-44-12	Size: 592 x 592 x 292	3400	4250	65	95	635
MERV 11 / M6	98	FVG6-04-12	FVGT6-04-12	Size: 490 x 592 x 292	2750	3450	65	95	635
MERV 11 / M6	98	FVG6-24-12	FVGT6-24-12	Size: 287 x 592 x 292	1700	2125	65	95	635

● Final Resistance : 635 Pa ● Burst Pressure : 6000 Pa ● Temperature : 80 ° C

All data are average indicative values with usual manufacturing and testing tolerances. We reserve the right to modify performance data without prior notices due to the constant technical improvement.

© Copyright: Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. We assume no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

